

**LAST-A-FOAM FR-3700, FR-4300, FR-4500,
FR-4600, FR-4700, FR-6700, FR-7100, FR-10100**

Revision: 05/26/2015

1. Product and Company Identification

Product Code: 00002
Product Name: LAST-A-FOAM FR-3700, FR-4300, FR-4500, FR-4600, FR-4700, FR-6700, FR-7100, FR-10100
Trade Name: Rigid Polyurethane Foam
Company Name: General Plastics Manufacturing Company **Phone Number:**
 4910 S. Burlington Way (253)473-5000
 Tacoma, WA 98409
Web site address: www.generalplastics.com
Email address: support@generalplastics.com

2. Hazards Identification

GHS Signal Word: None
GHS Hazard Phrases:
GHS Precaution Phrases:
GHS Response Phrases:
GHS Storage and Disposal Phrases:
Potential Health Effects (Acute and Chronic): Fine dust can be irritating due to mechanical action in the eye.
 Dust masks can be worn if fine dust irritated throat.
Inhalation: Dust may cause irritation to upper respiratory tract.
 Dust or fumes from cutting, sanding or grinding operations may be irritating to upper respiratory tract and lungs.
Skin Contact: Unlikely due to form.
Eye Contact: Dust may be irritation to eye due to mechanical action.
Ingestion: Not likely due to form.

3. Composition/Information on Ingredients

CAS #	Hazardous Components (Chemical Name)	Concentration	
NA	Polyurethane Cellular Polymer	100.0 %	

4. First Aid Measures

Emergency and First Aid Procedures:
In Case of Inhalation: Move victim to fresh air.
In Case of Skin Contact: Wash with plenty of soap and water.
In Case of Eye Contact: Hold eyelids apart and flush eyes with plenty of water. After initial flushings, remove any contact lenses and continue flushing for at least 15 minutes. Mechanical effects only.
In Case of Ingestion: IF SWALLOWED: In large amounts, consult a physician and follow their instructions.
Signs and Symptoms Of Exposure: Irritated eyes.
 Coughing, irritated throat.

**LAST-A-FOAM FR-3700, FR-4300, FR-4500,
FR-4600, FR-4700, FR-6700, FR-7100, FR-10**

Printed: 08/18/2015
Revision: 05/26/2015

5. Fire Fighting Measures

Flash Pt:

Explosive Limits: LEL: UEL:

Autoignition Pt: > 500.00 F

Suitable Extinguishing Media: Dry chemical, CO₂, sand, earth, water spray or regular foam.

Fire Fighting Instructions: Use NIOSH/MSHA approved positive pressure self-contained breathing apparatus when any material is involved in a fire. Evacuate area and fight fire from a safe distance.

Flammable Properties and Hazards: Although the FR grades are self extinguishing by a test method, the material can be consumed by fire of sufficient heat and intensity.

Hazardous Combustion Products: hydrogen cyanide nitrogen oxides, carbon monoxide and other potentially hazardous organic fragments resulting from incomplete combustion.

6. Accidental Release Measures

Steps To Be Taken In Case

Material Is Released Or

Spilled:

7. Handling and Storage

Precautions To Be Taken in Handling:

Precautions To Be Taken in Storing: Store in a cool dry place. Direct exposure to sunlight will cause color change and surface degradation.

8. Exposure Controls/Personal Protection

CAS #	Partial Chemical Name	OSHA TWA	ACGIH TWA	Other Limits
NA	Polyurethane Cellular Polymer			

Respiratory Equipment (Specify Type): An approved dust mask may be worn if needed.

Eye Protection: Eye protection is recommended.

Protective Gloves:

Other Protective Clothing:

Engineering Controls (Ventilation etc.): Provide general local exhaust to minimize dust.

9. Physical and Chemical Properties

Physical States: [] Gas [] Liquid [X] Solid

Appearance and Odor: Cellular solid of various colors. No noticeable odors.

pH: NP

Melting Point: NA

Boiling Point: NP

Flash Pt:

Evaporation Rate: NP

Flammability (solid, gas):

Explosive Limits: LEL: UEL:

Vapor Pressure (vs. Air or mm Hg): NP

Vapor Density (vs. Air = 1): NP

**LAST-A-FOAM FR-3700, FR-4300, FR-4500,
FR-4600, FR-4700, FR-6700, FR-7100, FR-10**

Printed: 08/18/2015
Revision: 05/26/2015

Specific Gravity (Water = 1):

Solubility in Water: NP
Saturated Vapor Concentration: NP
Percent Volatile: N.A.
Autoignition Pt: > 500.00 F
Decomposition Temperature: Unknown
Viscosity: NP

10. Stability and Reactivity

Reactivity: Essentially inert.
Stability: Unstable [] Stable [X]
Conditions To Avoid - Instability: Avoid heating above 350 F or for FR-4700 about 450 F.
Incompatibility - Materials To Avoid: Strong acids and bases. Strong oxidizers
Hazardous Decomposition or Byproducts: Depends on temperature, oxygen/air. Hazardous fumes can be generated.
Possibility of Hazardous Reactions: Will occur [] Will not occur [X]
Conditions To Avoid - Hazardous Reactions:

11. Toxicological Information

Toxicological Information: Dust may cause eye irritation and corneal injury due to mechanical action.
Sensitization: None anticipated.
Carcinogenicity: NTP? No IARC Monographs? No OSHA Regulated? No

12. Ecological Information

General Ecological Information: Not classified as environmentally hazardous to fish, plants, birds and aquatic organisms.
Persistence and Degradability: Not biodegradable. Will break down in direct exposure to sunlight.
Bioaccumulative Potential: Molecular weight >1000. Not expected to be bioaccumulative.
Mobility in Soil: Insoluble in water.

13. Disposal Considerations

Waste Disposal Method: Dispose of in accordance with local, state and federal regulations.

14. Transport Information

LAND TRANSPORT (US DOT):

DOT Proper Shipping Name: Polyurethane foam
DOT Hazard Class:
UN/NA Number:

LAND TRANSPORT (Canadian TDG):

TDG Shipping Name:
UN Number:
Hazard Class: **TDG Classification:**

**LAST-A-FOAM FR-3700, FR-4300, FR-4500,
FR-4600, FR-4700, FR-6700, FR-7100, FR-10**

Printed: 08/18/2015
Revision: 05/26/2015

MARINE TRANSPORT (IMDG/IMO):

IMDG/IMO Shipping Name:

UN Number:

Hazard Class:

Packing Group:

IMDG MFAG Number:

IMDG EMS Page:

Marine Pollutant:

No

15. Regulatory Information

Regulatory Information: Not a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29CFR 1910.1200

16. Other Information

Revision Date: 05/26/2015

Additional Information About

This Product:

Company Policy or

Disclaimer:

LAST-A-FOAM series rigid cellular plastics are closed cell and the last two digits denote the density in pounds per cubic foot.