


J2 LED Lighting, LLC

www.j2ledlighting.com

Product Specification Sheet

Micro Effects Light, LED

J2 LED Lighting, LLC P/N: MEL-WW1 (Warm White)



Characteristics

- 1) DC Barrel Connector female Jack accepts 2.1mm x 5.5mm plug with center positive.
- 2) Body shell: ABS (black).
- 3) Volts DC (VDC): 9-12 nominal (continuous), Max 12.5
- 4) Current (ref.): 20ma @ 9 VDC, 28ma @ 12 VDC, 30ma Max.
- 5) Power (nominal): 0.18 watts at 9 VDC, 0.34 watts at 12 VDC, 0.38 watts Max.
- 6) Output: Warm White (4 lumen ref., high intensity, 30 degree lens, clear)
- 7) Color Coordinates CIE1931: x=0.41/y=0.37 (3,200 Kelvin Typ.)

Notes / Cautions

- 1) Intense light source, for eye safety do not look directly into the beam at close range.
- 2) This lighting device is static sensitive, retain protective shipping bag for storage to protect from ESD (Electro Static Discharge) damage.
- 3) Observe correct polarity when connecting power, damage may result from unintended reverse polarity.
- 4) Device meets Rohs requirements

Plug 2.1mm X 5.5mm



Mating plug example
(Not included, sold separately)

J2 LED Lighting, LLC P/N: MEL-WW1 (Warm White)
Micro Effects Light, LED DC Barrel Connector
Rev-A (06/04/14)